


CEP Showcase


Piping System Design & Analysis



Brochure describes COADE's CAESAR II program for evaluating piping systems. CAESAR II applies rules of all major piping safety codes. Along with piping analysis, you receive related NEMA, API and WRC assessments; buried pipe analysis; structural steel modeling; hanger sizing; materials and component databases; and a direct link to the company's CAD package — CADWorx/PIPE. **Visit www.coade.com to download working demo.**

Reader Service Number # 150

Chemical Engineering Modeling Tool



COMSOL, Inc.'s FEMLAB puts you on the front line! FEMLAB Chemical Engineering comprises a powerful, unique environment for modeling momentum, heat and mass transport coupled to chemical reactions. Now you can model fluid flow, gas flow and incompressible turbulent flow using a single tool. FEMLAB's key features include: simultaneous solving of an arbitrary number of coupled nonlinear PDEs

and state-of-the-art solvers for linear and nonlinear stationary and time-dependent problems in 1D, 2D, and 3D.

Reader Service Number # 151

Therminol VLT



Therminol VLT is the first synthetic fluid to allow liquid-phase cooling at -115°C , as well as the flexibility of single-fluid cooling and heating in systems up to 175°C . The product also offers a viscosity of 45 cP at -115°C , which allows for efficient heat transfer and pumpability at extremely low temperatures. **For more information, call 1-800-433-6997 or visit www.therminol.com**

Reader Service Number # 152

TSWEET®



Process simulation software makes plant operations, troubleshooting and optimization easier - Experience the difference of the TSWEET®- PROSIM® package and enjoy the power our software can offer your company. • Amine Sweetening, Sulfur Recovery, Tail Gas Clean-up, Sour Water Strippers, Exchanger Rating/Sizing • Gas Processing, Refining, Petrochemical, Glycol Dehydration and Hydrate Inhibition. **Bryan Research & Engineering, Inc. Tel: 979-776-5220 www.bre.com**

Reader Service Number # 153

Ultrasonic Level Transmitter



ABM series ultrasonic level transmitters feature all PVC construction and ranges up to 60 feet. One push-button easily sets up the unit in the tank or on the bench. Self-cleaning transducer is immune to condensation build-up. Built in temperature compensation and false echo rejection is standard. AC or DC supply; 4-20mA output.

For additional information contact: [BABBITT INTERNATIONAL](http://www.babbittlevel.com), P. O. BOX 70094, HOUSTON, TX 77270 800-835-8012

Reader Service Number # 154

Molecular Weight in 3 Minutes



Viscotek's Flow Injection Polymer Analysis (FIPA) technique delivers fast and accurate average molecular weight and intrinsic viscosity in 3-5 minutes — without the need for elaborate sample preparation. FIPA provides the perfect complement to your current testing methods. Short sample turn-around time means it can be used for high throughput screening as well as routine process and

quality control. **For more information call us at 1-800-375-5966 or visit us at www.viscotek.com**

Reader Service Number # 155